

Application
for
United States Patent

To all whom it may concern:

Be it known that, Ohler L. Kinney, Jr., Robert S. Glauz, Brian F. Wright, Kathryn L. Pullen, and Eldon F. Mockry have invented certain new and useful improvements in

Cooling Tower Top Method and Apparatus

of which the following is a full, clear and exact description:

Cooling Tower Top Method and ApparatusPRIORITY

[0001] This application claims priority to the provisional U.S. patent application entitled, COOLING TOWER METHOD AND APPARATUS, filed November 2, 2001, having a serial number 60/330,896, the disclosure of which is hereby incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention relates generally to a method and apparatus for the disposal of heat utilizing a heat exchange liquid. More particularly, the present invention relates to a method and apparatus for a cross-flow water cooling tower wherein the water cooling tower is employed, for example, to dispose of large quantities of heat generated by various industrial processes.

BACKGROUND OF THE INVENTION

[0003] Cooling towers are used in many applications. For example, air conditioning systems for large buildings employ cooling towers for carrying out a portion of the heat exchange that is essential to the cooling process. Industrial processes, such as chemical production, metals production, plastics production, food processing, etc., generate heat that must be disposed of, often by the use of cooling towers. The cooling tower is a housing that channelizes air in proximity to a heat exchange liquid, for example, water. A heat exchange fluid may be circulated through the cooling tower and at least one fan may be mounted on the cooling tower to produce a flow of cooling air in proximity to the heat exchange liquid. Heat is transferred from the heat exchange fluid

to the air, largely through the evaporation of a small percentage of fluid which substantially lowers the temperature of the primary heat exchange fluid. The cooled heat exchange fluid can then return to the industrial process to perform a heat exchange function for either industrial processes or commercial air conditioning systems.

[0004] Conventional cross-flow cooling towers are presently in widespread use in such areas as factory complexes, chemical processing plants, hospitals, apartment and/or condominium complexes, warehouses and electric generating stations. Conventional cross-flow cooling towers are constructed with upright unitary or sectionalized fill structures surmounted by hot water distribution basins and cold water collection basins. The hot water basins are usually equipped with target nozzles or other hot water distributors which distribute the incoming water over the fill. The interior space bounded by the fill structures and the cold water basins define the plenum for the tower. A fan assembly made up of an apertured horizontal deck, which supports an upright, venturi-shaped stack, is positioned at the upper opening of the water cooling tower. This configuration provides a plenum large enough to enable a smooth transition of the flow gas from the generally horizontal direction, through the fill assembly, to the generally vertical direction, and out the exhaust port of the tower assembly. In the operation of the cross-flow cooling towers, hot water is introduced at the top of the fill while the air is introduced along the upright sides of the tower. As the water descends in an even distribution along the fill section, the cooling cross-flow air currents intersect the descending water in a heat exchanging relation. Subsequently, the cooled water is collected in a water basin below while the hot, moist air is discharged into the atmosphere.

[0005] In a cross-flow cooling tower, there is no necessity for the air to make radical changes of direction into the fill and the air inlet is spaced along the entire height of the fill. Therefore, the overall air pressure losses in the fill are usually less than those of a conventional counter-flow tower resulting in the passing of air through the tower more easily.

[0006] Conventional cross-flow cooling towers generally employ various varieties of splash-type fill sections consisting of elongated bars of a specific configuration for dispersing the descending released water. More recently, film type fill sections have been developed which have proven substantially more efficient than splash fill sections. These typically corrugated film fills generally consist of a series of thin, opposed sheets formed of synthetic resin materials in which water passes along the sheets of "film".

[0007] The highest potential for cooling exists at the top of the air inlet sides where the hottest water comes into contact with the coldest air. Once such air has been heated such that the wet bulb temperature of the air is near the water temperature, the air has no more capacity to cool the water, and such heat saturated air prevents the introduction of cooler ambient air into the fill. Air near the top of the tower typically experiences this condition because it initially contacts the hottest water, and all other water along its path of travel is about the same temperature. Air entering near the bottom of the tower initially is exposed to water that has been significantly cooled. As it traverses through the fill, the temperature of the water encountered by the bottom air currents rises, which allows the air to take on more heat.

[0008] The hot water basins in a cross-flow tower are normally constructed to serve as an air seal to prevent air entering the tower through the top of the fill. Additionally, air seals along the length of the tower are provided along the inboard and outboard edges of the basins to seal from the bottom of the basins to the top of the fill. These seals prevent air from entering the spray chamber and bypassing the fill structure. Sealing of the distribution basins also minimizes the contact between incoming air currents and relatively large water particles adjacent the spray nozzles or water distributors.

[0009] Presently, a majority of unitary cooling towers are assembled from a plurality of pieces of sheet metal that are mounted to a metallic support frame. Unitary cooling towers typically are manufactured at a location remote from the installation site. The towers are then shipped to the installation site in a substantially assembled form. Due to the metallic materials with which the cooling towers are assembled, the towers are fairly heavy and therefore require extensive structural support. In addition, the cost of present cooling towers are also adversely affected by the labor intensive processes for manufacturing and assembling the various metallic components of the cooling towers.

[0010] Metallic cooling towers are also subject to corrosion and/or rust. Thus, the metallic towers have a relatively short operational life. Corrosion and/or rust problems can be deterred by employing corrosion and/or rust resistant alloys. However, these metallic materials significantly increase the manufacturing cost of the water cooling tower. Alternatively, plastics such as polyethylene are well known for being moldable into prescribed form and function and are utilized in the art. However, polyethylene material properties are relatively weak and flexible. To compensate for these properties

in monolithic parts, designers must use large quantities of polyethylene to create bigger, thicker and deeper sections to minimize stresses and deflections.

[0011] Accordingly, it is desirable to provide a cooling tower design that offers a substantial reduction in parts, avoiding complex and costly assembly of components. It is also desirable to manufacture a water cooling tower that is light in weight, durable and resists corrosion.

SUMMARY OF THE INVENTION

[0012] The foregoing needs are met, to a great extent, by the present invention where, in one aspect, a cross-flow cooling tower is provided having a frame assembly that is unitarily molded from a plastic material. The frame assembly has opposed top and bottom walls that are parallel to one another along with opposed, parallel side walls that extend between the top and bottom walls. The frame assembly also has opposed, parallel ends that similarly extend between the top and bottom walls. The cross-flow cooling tower additionally has a vertical stack that extends vertically from the top wall. The top covers of the cross-flow cooling tower project outwardly and downwardly from the vertical stack, contacting the side walls and the opposing ends of the water cooling tower.

[0013] In accordance with another aspect of the present invention, a frame assembly is provided having a shell unitarily molded from plastic material. The unitary shell includes opposed parallel top and bottom walls along with opposed parallel ends. The aforementioned side walls and ends both extend between the top and bottom walls.

[0014] In accordance with yet another aspect of the present invention, a top for a cooling tower is provided having a hot liquid inlet and a generally planar bottom with at least one opening therein for accommodating an air current generator. In addition, the planar bottom has a plurality of hot liquid distributors oriented to distribute hot liquid. The cooling tower top additionally has opposed parallel side walls unitarily connected to the bottom wall. In addition, the cooling tower top has opposed, parallel end walls connected to the bottom wall. The aforementioned side and end walls are unitarily connected to a top wall wherein the top wall has at least one opening formed therein for accommodating an air current generator. The top wall projects outwardly and downwardly from the opening.

[0015] There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0016] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0017] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a perspective view of a cross-flow cooling tower in accordance with a first embodiment of the present invention.

[0019] FIG. 2 is a perspective view of a rotationally molded unitary frame assembly of the first embodiment of the present invention with tower covers unitarily attached to the opposing frame ends.

[0020] FIG. 3 is a top view of a top tower cover in accordance with the first embodiment of the present invention after the cover has been detached from an opposing end of the unitary frame assembly illustrated in FIG. 2.

[0021] FIG. 4 is a perspective view of the rotationally molded unitary frame assembly of the first embodiment of the present invention with the tower covers removed from the frame ends revealing the air intake ports of the frame assembly.

[0022] FIG. 5 is a perspective view of a cross-flow cooling tower in accordance with the first embodiment of the present invention with the rotationally molded unitary frame assembly shown in phantom.

[0023] FIG. 6 is a side cross-sectional view of a cross-flow cooling tower according to the first embodiment employing a rotationally molded, unitary frame assembly with top covers.

[0024] FIG. 7 is a perspective view of a second embodiment of a cross-flow cooling tower in accordance with the present invention.

[0025] FIG. 8 is a perspective view of a hot water distribution unit in accordance with the second embodiment of present invention.

[0026] FIG. 9 is a partial, cutaway view of the hot water distribution unit in accordance with the second embodiment of the present invention and showing a distribution pan or tray contained therein.

[0027] FIG. 10 is a perspective view of the underside of the hot water distribution unit of FIG. 9 in accordance with the second embodiment of the present invention.

[0028] FIG. 11 is a perspective view of an alternative two-piece hot water distribution unit in accordance with the second embodiment present invention.

[0029] FIG. 12 is a top view of a cold water collection basin in accordance with the second embodiment of present invention.

[0030] FIG. 13 is a perspective view a flow splitter employed in a preferred embodiment of the present invention.

[0031] FIG. 14 is a perspective view of a flow splitter employed in a preferred embodiment of the present invention.

[0032] FIG. 15 is a perspective view of two liquid collection basins that are molded together as one entity and then separated in accordance with an alternative embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED

EMBODIMENTS OF THE INVENTION

[0033] Referring now to the figures wherein like reference numerals indicate like elements, FIGS. 1-15 illustrate the presently preferred embodiments of a cross-flow cooling tower. While in the embodiment depicted the tower is a water cooling tower, it should be understood that the present invention is not limited in its application to water cooling towers, and can be used for other types of cooling towers.

[0034] Referring now to the first embodiment illustrated in FIGS. 1-6, a cross-flow cooling tower, generally designated 10, is illustrated for contacting generally horizontally flowing gas in a cooling relationship with generally vertically descending liquid. As seen in FIG. 4, the cooling tower includes a frame assembly 12 that is unitarily molded from polyethylene in a rotational mold, illustrated in FIG. 2, having a top 14, a bottom 16, two opposed side walls 18 and two opposed ends 20. More particularly, as seen in FIGS. 1-6, the tower is made up of a unitarily molded polyethylene frame assembly 12 reinforced by a mill galvanized steel skeleton 24, two upright fill assemblies 26, a hot water distributor 28 located above the fill assemblies 26, a vertical stack 30 extending upwardly from the hot water distributor 28, a cold water collection basin 32 below the fill assemblies 26, air intake ports 36, an exhaust port 39 and a cooling air current generator employing a fan unit 37. Skeleton 24 may be composed of other suitable materials such as stainless steel, hot dipped galvanized steel, epoxy coated steel, FRP (fiber reinforced plastic), etc. Fill assemblies 26 extend across the entire faces of air

intake ports 36. Only a few fill sheets are shown in assemblies 26 to add clarity to the structural features of tower 10.

[0035] After removal of the covers 34, the unitary frame assembly 12 includes two opposed side walls 18 that extend parallel to one another and are unitarily connected to a bottom generally planar wall and a top planar wall. The side walls 18 intersect the top generally planar wall to form the sides of the hot water distributor 28 above the fill assemblies 26 and intersect the bottom generally planar wall to form the side walls of the cold water collection basin 32 below the fill assemblies 26. As can be observed in FIG. 2, the opposed ends 20 of the frame assembly 12 intersect both the top and bottom generally planar walls of the cooling tower, forming the end barriers to the hot water distributor 28 and the cold water collection basin 32 respectively.

[0036] As illustrated in FIG. 2, initially, the unitarily polyethylene frame 12 is rotationally molded having solid opposing ends 20 wherein the cooling tower covers 34 are molded to be included within the opposing ends 20. Upon completion of the molding process, the solid opposing ends 20 and the tower covers 34 connected therein, are removed from the unitary frame 12 by a cutting means. The tower covers 34 are then prepared for installation and assembly above the hot water distributor 28. As a result of the removal of the tower covers 34, the opposing ends 20 of the cooling tower are designated air intake ports 36 when the tower is in operation. The aforementioned rotational molding of the unitary frame body 12 and following removal of the tower covers 34 offers a cost effective way for manufacturing and assembling a cross-flow water cooling tower by limiting the waste of manufacturing materials and by substantially reducing the amount of parts and assembly required.

[0037] In lieu of molding the tower covers 34 in opposed ends 20, louvers to prevent splash out of water may be molded into this face. Air inlet openings may be fabricated by removing the material around the intended louver structure. Molding the louvers in this face negates the requirement for attaching separate louvers or providing fill with integral louvers.

[0038] As illustrated in FIG. 4, the unitarily molded frame assembly 12 includes a hot water distributor 28 with a vertical stack 30 extending vertically therefrom and a cold water collection basin 32 disposed below the distributor. The frame 12 additionally includes two opposing side walls 18 that extend parallel to one another between the collection basin 32 and hot water distributor 28. The assembly also has two opposing intake ports 36.

[0039] The hot water distributor 28 contains a distribution pan or tray 38 positioned directly above the fill assemblies that permits water to gravitate through a plurality of apertures, perforations and/or nozzles 41 onto the top surfaces of the upper film sections of the fill assemblies 26. The water is supplied to the distribution pan or tray by way of supply pipe (not shown) and enters the assembly via the water inlet 40 shown in FIG. 1. Water is delivered to hot water distributor 28 and is distributed evenly to both sides with the aid of a generally inverted "V" shaped flow splitter 90 as illustrated in FIGS. 13 and 14. Flow control devices or valves are not required to balance the flow. Flow splitter 90 divides the flow and provides a barrier to prevent transitory or oscillatory flow variation from side to side.

[0040] The cold water collection basin 32 is disposed below the fill assemblies 26 in a position to receive liquid gravitating therefrom. The basin extends across the

entire width of the cooling tower 10 and may be coupled to a pumping structure (not shown) suitable for removing deposited liquid therein and for delivering the water to equipment requiring the same for cooling and/or returning the water to the supply source.

[0041] Referring now to FIG. 5, the polyethylene frame of the cooling tower 10 and components contained therein, are supported by conventional mill galvanized steel framework 24 as shown. The framework 24 offers support and strength to the tower frame while making the tower more durable, extending the cooling tower's operational life.

[0042] Polyethylene is a well-known plastic material used substantially for liquid containers such as milk jugs, and gallon gasoline containers. Polyethylene is a relatively inexpensive plastic and is dependable for containing liquids at low-pressure. However, polyethylene has relatively low material mechanical properties. The modulus of elasticity is only about 80,000 psi to 100,000 psi. By contrast the modulus of elasticity of steel is 29,000,000 psi which is about 300 times that of polyethylene. The implications for deflections are huge. For simple beams of the same geometry and loading, the one made of polyethylene will deflect 300 times the deflection of the steel beam. Therefore, to limit the deflections of polyethylene structures, the unsupported spans must be reduced very substantially and/or the cross-section increased very substantially compared to steel structures.

[0043] For example a simply supported beam subjected to a uniform load experiences a maximum deflection, Δ , according to following equation:

$$\Delta = 5 w L^4 / (384 EI) \dots\dots\dots(1)$$

in which

w = uniform load per unit length

L = length of simple span

E = modulus of elasticity

I = moment of inertia of the beam cross-section

To maintain the same deflection for a given span, L , and given uniform load, w , the product of EI for each beam must be constant:

$$E_p I_p = E_s I_s \dots\dots\dots(2)$$

in which subscripts p and s are polyethylene and steel respectively.

Solving for the required polyethylene moment of inertia gives the following equation:

$$I_p = I_s E_s / E_p \dots\dots\dots(3)$$

Taking the modulus of elasticity as 29,000,000 psi for steel and 100,000 psi for polyethylene, the required polyethylene beam moment of inertia is

$$\begin{aligned} I_p &= I_s (29,000,000 / 100,000) \\ &= 290 I_s \dots\dots\dots(4) \end{aligned}$$

For a simple rectangular beam cross-section the moment of inertia is computed as follows:

$$I = bh^3/12 \dots\dots\dots(5)$$

in which

b = beam width

h = beam height

Assuming a constant proportion of the width, b , to the height, h , the moment of inertia can be rewritten as:

$$I = \alpha h^4 / 12 \dots\dots\dots(6)$$

in which

$$\alpha = b/h \quad \text{or} \quad b = \alpha h$$

Substituting equation 6 with respective subscripts for steel and polyethylene in equation 4 and solving for the height of the polyethylene beam cross-section gives the following equation:

$$h_p = (290 h_s^4)^{0.25} \\ = 4.13 h_s \dots\dots\dots(7)$$

Therefore, the cross-section of the polyethylene beam must be over 4 times wider and over 4 times higher to carry the same load and maintain the same deflection for a given span.

The cross-sectional area, A, for the rectangular cross-section is

$$A = b h \dots\dots\dots(8)$$

Substituting the proportionality constant expression, $b = \alpha h$, from equation 6 gives the equation

$$A = \alpha h^2 \dots\dots\dots(9)$$

The cross-sectional area of the polyethylene beam, A_p , is

$$A_p = \alpha h_p^2 \\ = \alpha (4.13 h_s)^2 \\ = 17.1 \alpha h_s^2 \\ = 17.1 A_s \dots\dots\dots(10)$$

Therefore, the cross-sectional area of the polyethylene beam is over 17 times that of the steel beam. The specific gravity of steel and polyethylene relative to water are about 7.85

and 0.94 respectively. Steel weighs about $7.85/0.94 = 8.4$ times as much as polyethylene for the same volume of material.

The volume of the beam, V , is

$$V = A L \dots\dots\dots(11)$$

The volume of the polyethylene beam may be expressed in terms of the volume of the steel beam as follows:

$$\begin{aligned} V_p &= A_p L \\ &= 17.1 A_s L \\ &= 17.1 V_s \dots\dots\dots(12) \end{aligned}$$

The weight of the beam is determined by multiplying the specific weight, γ , times the volume.

$$W_s = \gamma_s V_s \dots\dots\dots(13)$$

$$W_p = \gamma_p V_p \dots\dots\dots(14)$$

$$\begin{aligned} W_p &= (\gamma_p/\gamma_s) \gamma_s (17.1 V_s) \\ &= 17.1 (\gamma_p/\gamma_s) W_s \dots\dots\dots(15) \end{aligned}$$

The specific weight of steel, γ_s , is 490 lb/cf, and the specific weight of polyethylene is about 59 lb/cf. Therefore, the weight of the polyethylene beam compared to the weight of the steel beam may be expressed as follows:

$$\begin{aligned} W_p &= 17.1 (59/490) W_s \\ &= 2.06 W_s \dots\dots\dots(16) \end{aligned}$$

Therefore, the polyethylene beam is actually more than twice the weight of the steel beam.

Furthermore, rotationally molded polyethylene costs more per unit weight than does fabricated heavy mill galvanized (HMG) steel per unit weight. Thus, it is not economical to directly replace an HMG steel beam with a polyethylene beam as it would cost more than twice as much.

[0044] The yield strength of polyethylene ranges from about 1300 psi to 2800 psi. The yield strength of steel is about 36,000 psi, which is about 28 to 13 times the strength of polyethylene. However, polyethylene is a viscoelastic material which creeps (or moves) under sustained load. Long term sustained stress levels must be kept low to prevent this viscoelastic behavior from causing unacceptable deflections over time. Steel does not creep and is not subject to this limitation.

[0045] Taking the beam example above for constant deflections, the maximum bending stress, f_b , may be computed from the following equation:

$$f_b = M/S \dots\dots\dots(17)$$

in which

$$M \equiv \text{bending moment} = w L^2/8 \dots\dots\dots(18)$$

$$S \equiv \text{section modulus} = b h^2/6 = \alpha h^3/6 \dots\dots\dots(19)$$

The section modulus of the polyethylene beam may be expressed in terms of the section modulus of the steel beam as follows:

$$\begin{aligned} S_p &= \alpha h_p^3/6 \\ &= \alpha (4.13 h_s)^3/6 \\ &= 70.4 (\alpha h_s^3/6) \end{aligned}$$

$$= 70.4 S_s$$

Therefore, since the bending moment is assumed constant for the example, the maximum bending stress in the polyethylene beam may be expressed in terms of the maximum bending stress of the steel beam as follows:

$$\begin{aligned} f_{bp} &= M/S_p \\ &= M/(70.4 S_s) \\ &= f_s/70.4 \end{aligned}$$

Steel members are often sized for a maximum stress of about 0.6 of the yield strength which is 0.6 (36,000 psi) = 21,600 psi. The polyethylene maximum bending stress would be 21,600 psi/70.4 = 307 psi. This is about 0.1 to 0.2 times the yield strength of the polyethylene, which normally is sufficient to control creep.

[0046] The structural comparisons above show that polyethylene is not economical for structural applications. On the other hand steel is very well suited for structural applications and has been used in a wide variety of applications including unitary cooling towers. Polyethylene is corrosion resistant and formable by rotational molding into multiple functional shapes. The two materials compliment one another in a structural hybrid cooling tower design to produce a cost effective, durable product. A steel skeleton provides load paths to support the polyethylene components.

[0047] As illustrated in FIG. 6, the fill assemblies 26 of the tower employ up to a total of two film type fill packs or units which are aligned in a duplicate fashion in two opposed units so as to present a double-flow tower. Each of the units is made up of a plurality of upright, spaced apart film fill sheets of chevron or herringbone design. The film fill sheets are integrally constructed to include both louvers and eliminators, which

for example, may be the type illustrated in U.S. Pat. No. 4,548,766. Each of the units and thus the overall fill assemblies 26, present upright air inlet faces 42, opposed, upright air outlet faces 44, and a generally horizontal upper face 46 extending between the inlet face 42 and the outlet face 44. Therefore as a result of the individual fill assembly orientation, the gas inlet 42 and outlet 44 openings enable the flow of gas over substantially the entire vertical height of the fill assembly into the central plenum chamber 48 of the water cooling tower 10.

[0048] Alternatively, the air inlet 42 faces may be provided with stationary louvers 50 utilized to prevent water from splashing out of the tower. Again, these louvers may be rotationally molded in opposed ends 20 in lieu of basin covers 34. A drift eliminator wall 52 can be disposed across the air outlet faces 44 and in generally an upright position to prevent entrained droplets of water from entering the plenum chamber 48 as spray. The wall may be of any type for example, a honey-comb type eliminator or a series of spaced inclined baffles that permit the free flow of air there through but prevent significant quantities of liquid droplets from escaping the fill assemblies 26. An exemplary eliminator is disclosed in U.S. Patent 4,514,202. The fill assemblies 26, in conjunction with their respective eliminator walls, combine to form the tower's central plenum 48.

[0049] FIG. 6 illustrates that a vertical stack 30 is disposed above the hot water basin 28 and extends upwardly from the central plenum chamber 48 to define the exhaust port 39 of the cooling tower 10. The fan unit 37 is positioned within the stack 30 and is supported by horizontal support members 54 wherein the fan unit 37 employs a blade assembly coupled to a motor. Operation of the fan unit 37 causes currents of air

to be drawn through the fill assemblies 26 and forces the currents upwardly through the plenum chamber 48 into the vertical stack 30 for discharge through the exhaust port 39.

[0050] A variety of alternative components and designs can be used in the water cooling towers of the present invention. FIG. 7 illustrates a second embodiment of the present invention wherein a cooling tower 56 is displayed having a steel frame assembly composed of mill galvanized steel, and having a top, a bottom, two opposed side walls, two opposed ends. More particularly, the tower consists of two opposed mill galvanized cold-formed steel side walls 58 parallel to one another, two upright fill assemblies 60, a self contained hot water distribution unit 62 above the fill assemblies 60, a cold water collection basin 64 below the fill assemblies 60, air intake ports 63, an exhaust port 65 and a cooling air current generator employing a fan unit 66.

[0051] Referring now to FIGS. 7-11, and in accordance with the present invention, the hot water distribution unit 62 is rotationally molded from polyethylene in one operation to produce a single, self enclosed unit that includes a generally planar, distribution pan or tray 68 having apertures, perforations and/or nozzles 69, four walls 70 unitarily connected to tower covers 72, and an opening 74 for tower exhaust. The covers 72 project outwardly and downwardly from the opening 74. More particularly, the distribution unit 62 is a self contained unit having a water inlet 76, a first set of opposing side walls 70 parallel to one another and second set of opposing sides walls 70 parallel to one another. Both sets of walls 70 extend vertically from the pan or tray 68 and intersect the tower covers 72 to form a unitary enclosure, employed for the distribution of hot water having a fan shroud 78. Raised portions 73 are designed to manage water delivered to distribution unit 62. Most importantly raised portions 73 serve

to transform the inlet piping flow discharge disturbances into a more quiescent channel flow which is then released into distribution pans or trays 68. Another significant benefit of raised portions 73 is reduction in the amount of water inventory carried in distribution unit 62, which reduces the operating weight. The distribution unit 62 may be attached to the galvanized steel frame of the water cooling tower 56 by fastening means such as screw, welding, bolt, solder, and/or bracket.

[0052] In addition, as illustrated in FIG. 11, should the tower be sufficiently large such that a single piece distribution unit 62 would be impractical to rotationally mold, the distribution unit 62 may be rotationally molded as two or more individual pieces 67 that are subsequently joined together to form a distribution unit 62.

[0053] Referring now to FIG. 12, the cold water collection basin 64 is disposed below the fill assemblies 60 in a position to receive liquid gravitating therefrom. The cold water basin 64 is a rotationally molded, unitary piece having a generally planar bottom surfaces 80 and 81, a first set of opposed side walls 82 extending parallel to one another away from the bottom surfaces 80, 81 and a second set of opposed side walls 84 extending parallel to one another away from the bottom surfaces 80, 81. The basin 64 extends across the entire width of the cooling tower and may be coupled to a pumping structure suitable for removing deposited liquid therein and for delivering the water to equipment requiring the same for cooling and/or returning the water to the supply source. The cold water basin 64 may be attached to the galvanized steel frame of the water cooling tower by fastening means such as screw, welding, bolt, solder, and/or bracket.

[0054] In addition, should the tower be sufficiently large such that a single piece collection basin 64 would be impractical to rotationally mold, the cold water

collection basin 64 may rotationally molded as two or more pieces that are subsequently joined together to form a collection basin 64.

[0055] In accordance with an alternative embodiment of the present invention, the hot water distribution unit 62 and collection basin 64 illustrated in FIGS. 7-11 may be rotationally molded together as one entity and then separated as illustrated in FIG. 15. As illustrated in FIG. 15, two basins 92 and 94 respectively, are rotationally molded simultaneously in a single molding process. The basins 92 and 94 are then separated by a cutting element. The basins are then incorporated into a water cooling tower assembly as previously described, wherein basin 92 is employed as a hot water distribution element and basin 94 is employed as a cold water collection basin.

[0056] The aforementioned molding process is advantageous because it allows for the creation of an enclosed mold which reduces the amount of waste produced during the molding process. If the basins were to be molded separately, a temporary top would be required to be molded for each piece so that the basin mold could be closed. The molded, temporary top portion would then have to be cut away from the basin to open it up resulting in wasted material. This embodiment does not include basin covers, however the covers may be fabricated separately and added to the tower assembly.

[0057] The many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirits and scope of the invention. Further, since numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction

and operation illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011
3012
3013
3014
3015
3016
3017
3018
3019
3020
3021
3022
3023
3024
3025
3026
3027
3028
3029
3030
3